

BATTERY TYPE NUMBER	VOLTAGE (V)	CAPACITY AH (10HR)	CHARGING TIME IN HOURS	WEIGHT WITHOUT ACID		ACID VOLUME (Liter)
			AT 1 AMP	Kg	Lbs	
CT7B-BS	12	6.5	2-5	1.85	4.07	0.34
CT9B-BS	12	8	4-8	2.43	5.35	0.38
CT12B-BS	12	11	5-10	3.12	6.87	0.51
CTZ10S-BS	12	9	4-8	2.32	5.11	0.42
CTZ12S-BS	12	11	5-10	3.18	7.00	0.53
CTZ14S-BS	12	11.2	5-10	3.18	7.00	0.53
CTR4A-BS	12	2.3	2-3	0.95	2.09	0.14
CT4L-BS	12	3	2-3	1.22	2.69	0.19
CTX4L-BS	12	3	2-3	1.25	2.75	0.19
CT5L-BS	12	4	2-5	1.60	3.52	0.24
CTX5L-BS	12	4	2-5	1.60	3.52	0.24
CTX7L-BS	12	6	3-6	2.00	4.41	0.34
CTX7A-BS	12	6	3-6	2.00	4.41	0.35
CTX9-BS	12	8	4-8	2.30	5.07	0.42
CTX12-BS	12	10	5-10	3.30	7.27	0.60
CTX14-BS	12	12	6-12	3.70	8.15	0.66
CTX14H-BS	12	12	6-12	4.20	9.25	0.66
CTX14L-BS	12	12	6-12	3.70	8.15	0.66
CTX14AH-BS	12	12	6-12	4.04	8.90	0.73
CTX14AHL-BS	12	12	6-12	4.04	8.90	0.73
CTX15L-BS	12	13	7-13	4.20	9.25	0.66
CTH16-12	12	14	7-14	4.22	9.30	0.80
CTX16-BS	12	14	7-14	4.22	9.30	0.80
CTX16-BS-1	12	14	7-14	4.22	9.30	0.80
CTX20CH-BS	12	18	9-18	4.69	10.33	0.80
CTX18-BS	12	21	11-21	5.80	12.78	1.20
CTX18L-BS	12	21	11-21	5.80	12.78	1.20
CTX20-BS	12	18	9-18	4.70	10.35	0.90
CTX20L-BS	12	18	9-18	4.70	10.35	0.90
CTX20H-BS	12	18	9-18	5.10	11.23	0.90
CTX20HL-BS	12	18	9-18	5.10	11.23	0.90
CTX16CL-B-BS	12	19	10-19	5.65	12.44	1.05
CTX19-BS	12	19	10-19	5.65	12.44	1.05
CTX19L-BS	12	19	10-19	5.65	12.44	1.05
CTX24HL-BS	12	21	11-21	6.10	13.44	1.20
CTX30L-BS	12	30	15-30	7.80	17.18	1.47
CTX30CL-B-BS	12	30	15-30	8.20	18.06	1.56